

LAMP BULBS & FLUORESCENT TUBES FITTED TO

L.T. CHISWICK WORKS, LONDON, W.4

LOCATION ON VEHICLE	R.M.F. R.M.L.		VEHICLE CODE					
	R.M.C.	R.M.	R.W.	G.S.	RLH.	RF(O.M.O)	RF(COACHES)	RF(
HEAD LAMP - OFFSIDE	A & B	C	C	C	F	C	E	
HEAD LAMP - NEARSIDE	A & B	C	C	C	F	C	C	
FOG LAMP	C	C	C	C	D	C	C	
SIDE LAMP	G	G	G	G	G	G	G	
TAIL LAMP	G	G	G	G	G	G	G	
STOP LAMP	J	J	J	J	J	J	J	
REGISTRATION NUMBER	G	G	G					
SPEEDOMETER LAMP	J	J		J	J	J	J	
STEP LAMP			G	G		G	C	
REVERSING LAMP			K	K		K		
REVERSING 'WARNING' LAMP			W					
INDICATOR 'REVERSING'			L	L		L		
CONDUCTORS PLATFORM	M	M			T			
SEMAPHORE TRAFFICATORS								
SIDE AND REAR FLASHERS	O	O	O	O	O	O	O	
FLASHER 'WARNING' LIGHT	P	P	P	P	P	P	P	
BLIND INDICATOR BOXES	J	J	J	J	J	J	J	
BULK HEAD ROUTE NUMBER								
UPPER SALOON	R	M			J			
LOWER SALOON - SIDE LIGHTS	R	M	J	S	T	T	T	
LOWER SALOON - CENTRE LIGHTS								
LUGGAGE COMPARTMENT								
CAB LIGHT	J	J	J					
TICKET MACHINE LAMP				T		T		
PRESSURE WARNING LAMP				G	G	G	G	
BRAKE & GEAR BOX WARNING LAMP	P	P	V					
DOOR WARNING LAMP	P		V					
REAR EMERGENCY DOOR WARNING LIGHT		R.M.F. ONLY P	W					
SALOON HEATER WARNING LIGHT				P	P			
PUBLIC ADDRESS WARNING LIGHT							G	
INSTRUMENT PANEL LAMP			V					
DYNAMO PILOT LAMP			V					
BLIND INDICATOR WARNING LAMP	P	P						

INDEX LETTER	VOLTS	WATTS	SIZE ^m / _m	CAP	PART No.	REMARKS	INDEX LETTER	VOLTS
A	24	37.5/50	—	B P F	CAV/2A.54520202	SEALED BEAM OUTER	N	24
B	24	50	—	B P F	- /IA 54520201	SEALED BEAM INNER	R	—
C	24	44	28 ^M / _M	B P F	24615-169		M	24
D	24	48	38 ^M / _M	S B C	24615-175	rect	T	24
E	24	54/44	28 ^M / _M	B P F	CAV/437		U	24
F	24	48	38 ^M / _M	BC	24615-174		P	28
G	30	6	38 ^M / _M	BC	24615-203		V	28
H	24	6	18 ^M / _M	S B C	24615-143		W	28
J	24	12	38 ^M / _M	BC	24615-147		X	16
K	24	24	25 ^M / _M	S B C	CAV/333		O	12
L	24	24	25 ^M / _M	S B C	416-435	SPOTTED	S	24

